

**PART 70 OPERATING PERMIT
AND ENHANCED NEW SOURCE REVIEW
OFFICE OF AIR MANAGEMENT**

**Lear Corporation, Shenandoah Division
500 North Fillmore Road
Greencastle, IN 46135**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 and 326 IAC 2-1-3.2 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T133-5083-00018	
Issued by: Felicia R. George, Assistant Commissioner Office of Air Management	Issuance Date:

TABLE OF CONTENTS

A	SOURCE SUMMARY	6
A.1	General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	6
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]	6
A.3	Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]	7
A.4	Part 70 Permit Applicability [326 IAC 2-7-2]	7
A.5	Prior Permit Conditions Superseded [326 IAC 2]	7
B	GENERAL CONDITIONS	8
B.1	Permit No Defense [326 IAC 2-1-10] [IC 13]	8
B.2	Definitions [326 IAC 2-7-1]	8
B.3	Permit Term [326 IAC 2-7-5(2)]	8
B.4	Enforceability [326 IAC 2-7-7(a)]	8
B.5	Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]	8
B.6	Severability [326 IAC 2-7-5(5)]	8
B.7	Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]	8
B.8	Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)]	8
B.9	Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]	9
B.10	Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)]	9
B.11	Annual Compliance Certification [326 IAC 2-7-6(5)]	9
B.12	Preventive Maintenance Plan [326 IAC 2-7-5][326 IAC 2-7-6][326 IAC 1-6-3]	10
B.13	Emergency Provisions [326 IAC 2-7-16]	11
B.14	Permit Shield [326 IAC 2-7-15]	12
B.15	Multiple Exceedances [326 IAC 2-7-5(1)(E)]	13
B.16	Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]	13
B.17	Permit Modification, Reopening, Revocation and Reissuance, or Termination	14
B.18	Permit Renewal [326 IAC 2-7-4]	14
B.19	Administrative Permit Amendment [326 IAC 2-7-11]	15
B.20	Minor Permit Modification [326 IAC 2-7-12]	15
B.21	Significant Permit Modification [326 IAC 2-7-12(d)]	16
B.22	Permit Revision Under Economic Incentives and Other Programs	16
B.23	Changes Under Section 502(b)(10) of the Clean Air Act [326 IAC 2-7-20(b)]	16
B.24	Operational Flexibility [326 IAC 2-7-20]	16
B.25	Construction Permit Requirement [326 IAC 2]	18
B.26	Inspection and Entry [326 IAC 2-7-6(2)]	18
B.27	Transfer of Ownership or Operation [326 IAC 2-1-6] [326 IAC 2-7-11]	18
B.28	Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]	18
B.29	Enhanced New Source Review [326 IAC 2]	19
C	SOURCE OPERATION CONDITIONS	20
	Emission Limitations and Standards [326 IAC 2-7-5(1)]	
C.1	Major Source	20
C.2	Opacity [326 IAC 5-1]	20
C.3	Open Burning [326 IAC 4-1] [IC 13-17-9]	20
C.4	Incineration [326 IAC 4-2] [326 IAC 9-1-2]	20
C.5	Fugitive Dust Emissions [326 IAC 6-4]	20
C.6	Operation of Equipment [326 IAC 2-7-6(6)]	20
C.7	Asbestos Abatement Projects - Accreditation [326 IAC 14-10] [326 IAC 18]	20
	Testing Requirements [326 IAC 2-7-6(1)]	

C.8	Performance Testing [326 IAC 3-2.1]	21
Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]		
C.9	Compliance Schedule [326 IAC 2-7-6(3)]	21
C.10	Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]	21
C.11	Monitoring Methods [326 IAC 3]	22
C.12	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]	22
Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]		
C.13	Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]	23
C.14	Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]	23
C.15	Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5(3)]	24
C.16	Actions Related to Noncompliance Demonstrated by a Stack Test	25
Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]		
C.17	Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-6] [326 IAC 2-7-19]	25
C.18	Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]	26
C.19	General Record Keeping Requirements [326 IAC 2-7-5(3)(B)]	26
C.20	General Reporting Requirements [326 IAC 2-7-5(3)(C)]	27
Stratospheric Ozone Protection		
C.21	Compliance with 40 CFR 82 and 326 IAC 22-1	28
D.1	FACILITY OPERATION CONDITIONS - Paint Line 1 and Paint Line 2	29
Emission Limitations and Standards [326 IAC 2-7-5(1)]		
D.1.1	Best Available Control Technology (BACT) [326 IAC 8-1-6]	29
D.1.2	PSD Minor Limit [326 IAC 2-2] [40 CFR 52.21]	29
D.1.3	Particulate Matter (PM) [326 IAC 6-3-2(c)]	29
D.1.4	Preventive Maintenance Plan [326 IAC 2-7-5(13)]	29
Compliance Determination Requirements		
D.1.5	Testing Requirements [326 IAC 2-7-6(1)]	29
D.1.6	Volatile Organic Compounds (VOC)	30
Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]		
D.1.7	Particulate Matter (PM)	30
D.1.8	Monitoring	30
Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]		
D.1.9	Record Keeping Requirements	30
D.1.10	Reporting Requirements	31
D.2	FACILITY OPERATION CONDITIONS - Glue Booths 1-7, 10, 12	32
Emission Limitations and Standards [326 IAC 2-7-5(1)]		
D.2.1	Best Available Control Technology (BACT) [326 IAC 8-1-6]	32
D.2.2	Particulate Matter (PM) [326 IAC 6-3-2(c)]	32
D.2.3	Preventive Maintenance Plan [326 IAC 2-7-5(13)]	32
Compliance Determination Requirements		
D.2.4	Testing Requirements [326 IAC 2-7-6(1)]	32
D.2.5	Volatile Organic Compounds (VOC)	32

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]	
D.2.6 Particulate Matter (PM)	33
D.2.7 Monitoring	33
Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]	
D.2.8 Record Keeping Requirements	33
D.2.9 Reporting Requirements	34
D.3 FACILITY OPERATION CONDITIONS - Paint at Press Booth, Glue Booths 22 and 23 ..	35
Emission Limitations and Standards [326 IAC 2-7-5(1)]	
D.3.1 Best Available Control Technology (BACT) [326 IAC 8-1-6]	35
D.3.2 PSD Minor Limit [326 IAC 2-2] [40 CFR 52.21]	35
D.3.3 Particulate Matter (PM) [326 IAC 6-3-2(c)]	35
D.3.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]	35
Compliance Determination Requirements	
D.3.5 Testing Requirements [326 IAC 2-7-6(1)]	35
D.3.6 Volatile Organic Compounds (VOC).....	36
Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]	
D.3.7 Particulate Matter (PM)	36
D.3.8 Monitoring	36
Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]	
D.3.9 Record Keeping Requirements	36
D.3.10 Reporting Requirements	37
D.4 FACILITY OPERATION CONDITIONS - Glue Booths 27-29	38
General Construction Conditions	38
Effective Date of the Permit	38
First Time Operation Permit	38
Emission Limitations and Standards [326 IAC 2-7-5(1)]	
D.4.5 Best Available Control Technology (BACT) [326 IAC 8-1-6]	39
D.4.6 PSD Minor Source Limit [326 IAC 2-2] [40 CFR 52.21]	39
D.4.7 Particulate Matter (PM) [326 IAC 6-3-2(c)]	39
D.4.8 Preventive Maintenance Plan [326 IAC 2-7-5(13)]	39
Compliance Determination Requirements	
D.4.9 Testing Requirements [326 IAC 2-7-6(1)]	39
D.4.10 Volatile Organic Compounds (VOC).....	39
Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]	
D.4.11 Particulate Matter (PM)	39
D.4.12 Monitoring	39
Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]	
D.4.13 Record Keeping Requirements	40
D.4.14 Reporting Requirements	40

D.5	FACILITY OPERATION CONDITIONS - Insignificant Combustion Sources	41
	Emission Limitations and Standards [326 IAC 2-7-5(1)]	
D.5.1	Particulate Matter (PM) [326 IAC 6 -2-4]	41
	Compliance Determination Requirements	
D.5.2	Testing Requirements [326 IAC 2-7-6(1)]	41
	Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]	
D.5.3	Compliance Monitoring	41
	Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]	
D.5.4	Record Keeping and Reporting Requirements	41
D.6	FACILITY CONDITIONS - Insignificant Activities	42
	Emission Limitations and Standards [326 IAC 2-7-5(1)]	
D.6.1	Volatile Organic Compound (VOC) [326 IAC 8-1-6]	42
D.6.2	Particulate Matter [326 IAC 6-3]	42
	Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]	
D.6.3	Compliance Monitoring	42
	Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]	
D.6.4	Record Keeping and Reporting Requirements	42
	Certification Form	43
	Emergency/Deviation Occurrence Report	44-45
	Quarterly Report Forms	46-48
	Compliance Report Form	49

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM), and presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

The Permittee owns and operates a stationary plant for the manufacture of injection molded plastic parts for use in automobile interiors.

Responsible Official: Dennis Hamilton, General Manager
Source Address: 500 North Fillmore Road. Greencastle, Indiana 46135
Mailing Address: 500 North Fillmore Road. Greencastle, Indiana 46135
SIC Code: 3089
County Location: Putnam
County Status: Attainment for all criteria pollutants
Source Status: Part 70 Permit Program
Major Source, under PSD Rules;
Major Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

- (1) One Ranger paint application line, identified as Paint Line 1, consisting of two (2) paint booths, 1 and 2, and one (1) curing oven, with a maximum capacity of 360 plastic parts per hour, with particulate matter overspray from each booth controlled by water curtain, and exhausting to stacks 1 and 2.
- (2) One S-Van paint application line, identified as Paint Line 2, consisting of two (2) paint booths, 3 and 4, and one (1) curing oven, with a maximum capacity of 420 plastic parts per hour, with particulate matter overspray from each booth controlled by water curtain, and exhausting to stacks 3, 4, and 5.
- (3) Nine (9) glue booths, identified as Glue Booth 1-7, 10 and 12, each with a maximum capacity of 125 plastic and fabric parts per hour, and exhausting to stacks 10, 12, 13, and 14. Glue Booths 5, 6, and 7 use dry filters for particulate matter overspray control.
- (4) One (1) paint at press booth, identified as PPB, equipped with high-volume low-pressure (HVLP) spray applicators with a maximum capacity of 130 plastic automotive parts per hour, with dry filters for overspray control, exhausting to stacks 21 and 22.
- (5) Two (2) glue booths, identified as Glue Booths 22 and 23, equipped with air atomization spray applicators, with dry filters for overspray control, and exhausting to stack 20 and two (2) bolster wrap machines, identified as Bolster Wraps 24 and 25, equipped with air atomization spray applicators, with dry filters for overspray control, and exhausting to stack 20. The combined maximum capacity of these units is 288 plastic automotive parts per hour.
- (6) Three (3) glue booths, identified as Glue Booths 27-29, each with a maximum capacity of 125 plastic and fabric parts per hour, with dry filters for control of particulate matter overspray, with Glue Booth 27 exhausting to stack 13, and Glue Booths 28 and 29 exhausting to stack 23.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21):

- (1) Natural gas-fired combustion sources with heat input equal to or less than ten (10) million Btu per hour (water boiler - 0.78 MMBtu/hr, water boiler - 1.092 MMBtu/hr, comfort heat boiler - 0.745 MMBtu/hr, space heaters).
- (2) Other categories with emissions below insignificant thresholds:
 - (a) Touch-up paint booth in "Ranger" paint room;
 - (b) Touch-up paint booth in "S-Van" paint room;
 - (c) Touch-up paint hood near pad printing room;
 - (d) Mask washer in "Ranger" paint room;

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

A.5 Prior Permit Conditions Superseded [326 IAC 2]

The terms and conditions of this permit incorporate all the current applicable requirements for all emission units located at this source, and supersede all terms and conditions in all registrations and permits, including construction permits, issued prior to the date of issuance of this permit. All terms and conditions in such registrations and permits are no longer in effect.

SECTION B

GENERAL CONDITIONS

B.1 Permit No Defense [326 IAC 2-1-10] [IC 13]

- (a) Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7.
- (b) This prohibition shall not apply to alleged violations of applicable requirements for which the Commissioner has granted a permit shield in accordance with 326 IAC 2-1-3.2 or 326 IAC 2-7-15.

B.2 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, 326 IAC 1-2 and 326 IAC 2-7 shall prevail.

B.3 Permit Term [326 IAC 2-7-5(2)]

This permit is issued for a fixed term of five (5) years from the effective date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3.

B.4 Enforceability [326 IAC 2-7-7(a)]

- (a) All terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM.
- (b) Unless otherwise stated, terms and conditions of this permit, including any provisions to limit the source's potential to emit, are enforceable by the United States Environmental Protection Agency (U.S. EPA) and citizens under the Clean Air Act.

B.5 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.6 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.7 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort, or any exclusive privilege.

B.8 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)]

- (a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall furnish to IDEM, OAM, within a reasonable time, any information that

IDEM, OAM, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit.

- (c) Upon request, the Permittee shall also furnish to IDEM, OAM, copies of records required to be kept by this permit. For information claimed to be confidential, the Permittee shall furnish such records to IDEM, OAM, along with a claim of confidentiality under 326 IAC 17. If requested by IDEM, OAM, or the U.S. EPA, the Permittee shall furnish such confidential records directly to the U.S. EPA along with a claim of confidentiality under 40 CFR 2, Subpart B.

Such confidentiality claim shall meet the requirements of 40 CFR 2, Subpart B (when submitting to U.S. EPA) and 326 IAC 17 (when submitting to IDEM, OAM).

B.9 Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit constitutes a violation of the Clean Air Act and is grounds for:
- (1) Enforcement action;
 - (2) Permit termination, revocation and reissuance, or modification; or
 - (3) Denial of a permit renewal application.
- (b) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

B.10 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)]

- (a) Any application form, report, or compliance certification submitted under this permit shall contain certification by a responsible official of truth, accuracy, and completeness. This certification, and any other certification required under this permit, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.11 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining compliance of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAM, may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.12 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this permit, including the following information on each:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission units and associated emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that lack of proper maintenance does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM.

B.13 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation,

except as provided in 326 IAC 2-7-16.

- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:

- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
- (2) The permitted facility was at the time being properly operated;
- (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAM, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Management, Compliance Section), or

Telephone Number: 317-233-5674 (ask for Compliance Section)

Facsimile Number: 317-233-5967

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted notice, either in writing or facsimile, of the emergency to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.

- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions) for sources subject to this rule after the effective date of this rule. This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAM, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAM, by telephone or facsimile of an emergency lasting more than one (1) hour in compliance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
 - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
 - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
 - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value.

Any operation shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

B.14 Permit Shield [326 IAC 2-7-15]

- (a) Compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided either of the following:
 - (1) The applicable requirements are included and specifically identified in this permit;
 - (2) IDEM, OAM, in acting on the Part 70 permit application or revision, determines in writing that other requirements specifically identified are not applicable to the source, and the Part 70 permit includes the determination or a concise summary thereof.
- (b) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application.
- (c) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement, IDEM, OAM, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit

shield shall continue in effect so long as the Permittee is in compliance with the compliance order.

- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
- (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (e) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (f) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAM, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (g) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAM, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.15 Multiple Exceedances [326 IAC 2-7-5(1)(E)]

Any exceedance of a permit limitation or condition contained in this permit, which occurs contemporaneously with an exceedance of an associated surrogate or operating parameter established to detect or assure compliance with that limit or condition, both arising out of the same act or occurrence, shall constitute a single potential violation of this permit.

B.16 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

within ten (10) calendar days from the date of the discovery of the deviation.

- (b) Written notification shall be submitted on the attached Emergency/Deviation Occurrence Reporting Form or its substantial equivalent.
- (c) Proper notice submittal under 326 IAC 2-7-16 satisfies the requirement of this subsection.

**B.17 Permit Modification, Reopening, Revocation and Reissuance, or Termination
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]**

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and

reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)]

- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAM, determines any of the following:
 - (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAM, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAM, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAM, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.18 Permit Renewal [326 IAC 2-7-4]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAM, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]
 - (1) A timely renewal application is one that is:
 - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due. [326 IAC 2-5-3]
 - (2) If IDEM, OAM, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

- (c) **Right to Operate After Application for Renewal** [326 IAC 2-7-3]
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAM, takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAM, any additional information identified as being needed to process the application.
- (d) **United States Environmental Protection Agency Authority** [326 IAC 2-7-8(e)]
If IDEM, OAM, fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and reissue a Part 70 permit.

B.19 Administrative Permit Amendment [326 IAC 2-7-11]

- (a) An administrative permit amendment is a Part 70 permit revision that makes changes of the type specified under 326 IAC 2-7-11(a).
- (b) An administrative permit amendment may be made by IDEM, OAM, consistent with the procedures specified under 326 IAC 2-7-11(c).
- (c) The Permittee may implement the changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.20 Minor Permit Modification [326 IAC 2-7-12]

- (a) A permit modification is any revision to this permit that cannot be accomplished as an administrative permit amendment under 326 IAC 2-7-11.
- (b) Minor modification to this permit shall follow the procedures specified under 326 IAC 2-7-12(b), except as provided by 326 IAC 2-7-12(c).
- (c) An application requesting the use of minor modification procedures shall meet the requirements of 326 IAC 2-7-12(b) and shall include the information required in 326 IAC 2-7-12(b)(3)(A) through (E).
- (d) The Permittee may make the change proposed in its minor permit modification application immediately after it files such application provided that the change has received any approval required by 326 IAC 2-1. After the Permittee makes the change allowed under minor permit modification procedures, and until IDEM, OAM, takes any of the actions specified in 326 IAC 2-7-12(b)(6)(A) through (C), the Permittee must comply with both the applicable requirements governing the change and the proposed permit terms and conditions. During this period, the Permittee need not comply with the existing permit terms and conditions it seeks to modify. If the Permittee fails to comply with its proposed permit terms and conditions during this time period, the existing permit terms and conditions it seeks to modify may be enforced against it. [326 IAC 2-7-12(b)(7)]

B.21 Significant Permit Modification [326 IAC 2-7-12(d)]

- (a) Significant modification procedures shall be used for applications requesting permit modifications that do not qualify as minor permit modifications or as administrative amendments.

- (b) Every significant change in existing monitoring permit terms or conditions and every relaxation of reporting or record keeping permit terms or conditions of this permit shall be considered significant.
- (c) Nothing in 326 IAC 2-7-12(d) shall be construed to preclude the Permittee from making changes consistent with 326 IAC 2-7 that would render existing permit compliance terms and conditions irrelevant.
- (d) Significant modifications of this permit shall meet all requirements of 326 IAC 2-7, including those for application, public participation, review by affected states, review by the U.S. EPA, and availability of the permit shield, as they apply to permit issuance and renewal.

B.22 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]
[326 IAC 2-7-12 (b)(2)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1)(D)(i) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.23 Changes Under Section 502(b)(10) of the Clean Air Act [326 IAC 2-7-20(b)]

The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a) and the following additional conditions:

- (a) For each such change, the required written notification shall include a brief description of the change within the source, the date on which the change will occur, any change in emissions, and any permit term or condition that is no longer applicable as a result of the change.
- (b) The permit shield, described in 326 IAC 2-7-15, shall not apply to any change made under 326 IAC 2-7-20(b).

B.24 Operational Flexibility [326 IAC 2-7-20]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:
 - (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
 - (2) Any approval required by 326 IAC 2-1 has been obtained;
 - (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
 - (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-7-20(b), (c), or (e) and makes such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAM, in the notices specified in 326 IAC 2-7-20(b), (c)(1), and (e)(2).

- (b) For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:
 - (1) A brief description of the change within the source;
 - (2) The date on which the change will occur;
 - (3) Any change in emissions; and
 - (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAM, or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited under, Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

B.25 Construction Permit Requirement [326 IAC 2]

Except as allowed by Indiana P.L. 130-1996 Section 12, as amended by P.L. 244-1997,

modification, construction, or reconstruction shall be approved as required by and in accordance with 326 IAC 2.

B.26 Inspection and Entry [326 IAC 2-7-6(2)]

Upon presentation of IDEM identification cards, credentials, and other documents as may be required by law, the Permittee shall allow IDEM, OAM, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.
[326 IAC 2-7-6(6)]

B.27 Transfer of Ownership or Operation [326 IAC 2-1-6] [326 IAC 2-7-11]

Pursuant to 326 IAC 2-1-6 and 326 IAC 2-7-11:

- (a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAM, Permits Branch, within thirty (30) days of the change. Notification shall include a written agreement containing a specific date for transfer of permit responsibility, coverage, and liability between the Permittee and the new owner.
- (b) The written notification shall be sufficient to transfer the permit to the new owner by an administrative amendment pursuant to 326 IAC 2-7-11.
- (c) IDEM, OAM, shall reserve the right to issue a new permit.

B.28 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]

- (a) The Permittee shall pay annual fees to IDEM, OAM, within thirty (30) calendar days of receipt of a billing, or in a time period consistent with the fee schedule established in 326 IAC 2-7-19.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) If the Permittee does not receive a bill from IDEM, OAM, thirty (30) calendar days before the due date, the Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-0425 (ask for OAM, Technical Support and Modeling Section), to determine the appropriate permit fee. The applicable fee is due April 1 of each year.

B.29 Enhanced New Source Review [326 IAC 2]

The requirements of the construction permit rules in 326 IAC 2 are satisfied by this permit for any

previously unpermitted facilities and facilities to be constructed within eighteen (18) months after the date of issuance of this permit, as listed in Sections A.2 and A.3.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Major Source

Pursuant to 326 IAC 2-2 (Prevention of Significant Deterioration, this source is a major source. This status includes those activities at the source that are considered insignificant activities.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Visible Emissions Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), visible emissions shall meet the following, unless otherwise stated in this permit:

- (a) Visible emissions shall not exceed an average of forty percent (40%) opacity in twenty-four (24) consecutive readings, as determined in 326 IAC 5-1-4.
- (b) Visible emissions shall not exceed sixty percent (60%) opacity for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3(a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2][326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Operation of Equipment [326 IAC 2-7-6(6)]

All air pollution control equipment listed in this permit shall be operated at all times that the emission units vented to the control equipment are in operation, as described in Section D of this permit.

C.7 Asbestos Abatement Projects - Accreditation [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

Prior to the commencement of any demolition or renovation activities, the Permittee shall use an Indiana accredited asbestos inspector to inspect thoroughly the affected facility or part of the facility where the demolition or renovation operation will occur for the presence of asbestos, including Category I and Category II nonfriable asbestos containing material. The requirement that the inspector be accredited is federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.8 Performance Testing [326 IAC 3-2.1]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-2.1 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing methods approved by IDEM, OAM.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days before the intended test date.

- (b) All test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by the Commissioner, if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.9 Compliance Schedule [326 IAC 2-7-6(3)]

The Permittee:

- (a) Will continue to comply with such requirements that become effective during the term of this permit; and
- (b) Has submitted a statement that the Permittee will continue to comply with such requirements; and
- (c) Has certified that all facilities at this source are in compliance with all applicable requirements.

C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment, no more than ninety (90) days after receipt of this permit. If due to circumstances beyond its control, this schedule cannot be met, the Permittee shall notify:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

in writing, no more than ninety (90) days after receipt of this permit, with full justification of the reasons for the inability to meet this date and a schedule which it expects to meet. If a denial of the request is not received before the monitoring is fully implemented, the schedule shall be deemed approved.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

C.11 Monitoring Methods [326 IAC 3]

Any monitoring or testing performed to meet the requirements of this permit shall be performed

according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.

C.12 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) asbestos removal or demolition start date;
 - (B) removal or demolition contractor; or
 - (3) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4 emission control requirements are mandatory for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Indiana Accredited Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited is federally enforceable.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.
- (b) These ERPs shall be submitted for approval to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

within ninety (90) days after the date of issuance of this permit.
- (c) If the ERP is disapproved by IDEM, OAM, the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP. If after this time, the Permittee does not submit an approvable ERP, then IDEM, OAM, shall supply such a plan.
- (d) These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.
- (e) Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.
- (f) Upon direct notification by IDEM, OAM, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present in more than the threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall:

- (a) Submit:
 - (1) A compliance schedule for meeting the requirements of 40 CFR 68 by the date provided in 40 CFR 68.10(a); or
 - (2) As a part of the compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP); and
 - (3) A verification to IDEM, OAM, that a RMP or a revised plan was prepared and submitted as required by 40 CFR 68.
- (b) Provide annual certification to IDEM, OAM, that the Risk Management Plan is being properly implemented.

C.15 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5(3)]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable

requirements. This compliance monitoring plan is comprised of:

- (1) This condition;
 - (2) The Compliance Determination Requirements in Section D of this permit;
 - (3) The Compliance Monitoring Requirements in Section D of this permit;
 - (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
 - (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAM upon request and shall be subject to review and approval by IDEM, OAM. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of :
 - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and
 - (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this permit, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the permit unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.
- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
- (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied or;
 - (3) An automatic measurement was taken when the process was not operating; or
 - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

C.16 Actions Related to Noncompliance Demonstrated by a Stack Test

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize emissions from the affected facility while the corrective actions are being implemented. IDEM, OAM shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAM within thirty (30) days of receipt of the notice of deficiency. IDEM, OAM reserves the authority to use enforcement activities to resolve noncompliant stack tests.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate permit conditions may be grounds for immediate revocation of the permit to operate the affected facility.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)][326 IAC 2-7-5(7)][326 IAC 2-7-19(c)][326 IAC 2-6]

- (a) The Permittee shall submit a certified, annual emission statement that must be received by July 1 of each year and must comply with the minimum requirements specified in 326 IAC 2-6-4. The annual emission statement shall meet the following requirements:
 - (1) Indicate actual emissions of criteria pollutants from the source, in compliance with 326 IAC 2-6 (Emission Reporting);
 - (2) Indicate actual emissions of other regulated pollutants from the source, for purposes of Part 70 fee assessment.
- (b) The annual emission statement covers the twelve (12) consecutive month time period starting January 1 and ending December 31. The annual emission statement must be submitted to:

Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015
- (c) The annual emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.

C.18 Monitoring Data Availability [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)]

- (a) With the exception of performance tests conducted in accordance with Section C- Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this permit shall be performed at all times the equipment is operating at normal representative conditions.

- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this permit is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this permit.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.
- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.

C.19 General Record Keeping Requirements [326 IAC 2-7-5(3)(B)]

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location and available within one (1) hour upon verbal request of an IDEM, OAM, representative, for a minimum of three (3) years. They may be stored elsewhere for the remaining two (2) years providing they are made available within thirty (30) days after written request.
- (b) Records of required monitoring information shall include, where applicable:
 - (1) The date, place, and time of sampling or measurements;
 - (2) The dates analyses were performed;
 - (3) The company or entity performing the analyses;
 - (4) The analytic techniques or methods used;
 - (5) The results of such analyses; and
 - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
 - (1) Copies of all reports required by this permit;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;
 - (4) Records of preventive maintenance shall be sufficient to demonstrate that improper maintenance did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such

violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan - Failure to take Response Steps, of this permit, and whether a deviation from a permit condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.

- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

- (a) To affirm that the source has met all the requirements stated in this permit, the source shall submit a Quarterly Compliance Report. Any deviation from the requirements and the date(s) of each deviation must be reported.

- (b) The report required in (a) of this condition, and reports required by conditions in Section D of this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.

- (d) Unless otherwise specified in this permit, any quarterly report shall be submitted within thirty (30) days of the end of the reporting period.

- (e) All instances of deviations must be clearly identified in such reports. A reportable deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:

- (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
- (2) An emergency as defined in 326 IAC 2-7-1(12); or
- (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
- (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred or failure to monitor or record the required compliance monitoring is a deviation.

- (f) Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.
- (g) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.

Stratospheric Ozone Protection

C.21 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1

FACILITY OPERATION CONDITIONS

- (1) One Ranger paint application line, identified as Paint Line 1, consisting of two (2) paint booths, 1 and 2, and one (1) curing oven, with a maximum capacity of 360 plastic parts per hour, with particulate matter overspray from each booth controlled by water curtain, and exhausting to stacks 1 and 2.
- (2) One S-Van paint application line, identified as Paint Line 2, consisting of two (2) paint booths, 3 and 4, and one (1) curing oven, with a maximum capacity of 420 plastic parts per hour, with particulate matter overspray from each booth controlled by water curtain, and exhausting to stacks 3, 4, and 5.

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Best Available Control Technology (BACT) [326 IAC 8-1-6]

Pursuant to 326 IAC 8-1-6 (BACT), Paint Line 1 and Paint Line 2 are subject to the use of low pressure-high volume spray equipment, with a transfer efficiency of no less than fifty-five percent (55%), and no coating containing greater than 6.1 pounds of VOC per gallon of coating, excluding water.

D.1.2 PSD Minor Source Limit [326 IAC 2-2] [40 CFR 52.21]

- (a) First Limitation - Pursuant to OP 67-02-92-0112, issued on March 1, 1988, the quantity of paint and solvent delivered to the applicator shall be such that VOC emissions from Paint Line 1 shall not exceed 10.33 tons per month. Compliance with this limit makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.
- (b) Second Limitation - Pursuant to OP 3520-0018-0132, issued on June 27, 1990, the quantity of paint and solvent delivered to the applicator shall be such that VOC emissions from Paint Line 2 shall not exceed 10.33 tons per month. Compliance with these limits makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.1.3 Particulate Matter (PM) [326 IAC 6-3-2(c)]

The PM from Paint Line 1 and Paint Line 2 shall each not exceed the pound per hour emission rate established as E in the following formula:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and any control devices.

Compliance Determination Requirements

D.1.5 Testing Requirements [326 IAC 2-7-6(1)]

If testing is required, compliance with the VOC limits specified in Condition D.1.1 and D.1.2 shall be determined by a performance test conducted in accordance with Section C - Performance Testing. Testing of this facility is not specifically required by this permit. However, this does not preclude testing requirements on this facility under 326 IAC 2-1-5 and 326 IAC 2-7-6.

D.1.6 Volatile Organic Compounds (VOC)

Compliance with the VOC content and usage limitations contained in Conditions D.1.1 and D.1.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3)(A) and 326 IAC 8-1-2(a)(7) using formulation data supplied by the coating manufacturer. IDEM, OAM reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.7 Particulate Matter (PM)

The water curtains for PM control shall be in operation at all times when Paint Line 1 or Paint Line 2 is in operation.

D.1.8 Monitoring

- (a) Daily inspections shall be performed to verify that the water flow rate is sufficient to produce a uniform water curtain.
- (b) Weekly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an overspray emission, evidence of overspray emission, or other abnormal emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plans.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.9 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1 and D.1.2, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.1.1 and D.1.2.
 - (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) A log of the dates of use;
 - (3) The cleanup solvent usage for each month;
 - (4) The total VOC usage for each month; and
 - (5) The weight of VOCs emitted for each compliance period.
- (b) To document compliance with Conditions D.1.7 and D.1.8, the Permittee shall maintain a log of daily water curtain inspections, and those additional inspections prescribed by the

Preventive Maintenance Plan.

- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.10 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.1.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported.

SECTION D.2

FACILITY OPERATION CONDITIONS

- (3) Nine (9) glue booths, identified as Glue Booth 1-7, 10 and 12, each with a maximum capacity of 125 plastic and fabric parts per hour, and exhausting to stacks 10, 12, 13, and 14. Glue Booths 5, 6, and 7 use dry filters for particulate matter overspray control.

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 Best Available Control Technology (BACT) [326 IAC 8-1-6]

- (a) Pursuant to CP 133-2380, issued on April 21, 1992, the VOC content of the glue supplied to the applicators of Glue Booths 6 and 7 shall not exceed a combined total of 2.0 tons per month. Compliance with this limit will make 326 IAC 8-1-6 (BACT) and 326 IAC 2-2 (PSD) not applicable to these facilities.
- (b) The VOC content of the glue supplied to the applicators of Glue Booths 10 and 12 shall not exceed a combined total of 2.0 tons per month. Compliance with this limit will make 326 IAC 8-1-6 (BACT) and 326 IAC 2-2 (PSD) not applicable to these facilities.

D.2.2 Particulate Matter (PM) [326 IAC 6-3-2(c)]

The PM from the Glue Booths (1-7, 10 and 12) shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

D.2.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for Glue Booths 6, 7, 10 and 12, and any control devices.

Compliance Determination Requirements

D.2.4 Testing Requirements [326 IAC 2-7-6(1)]

If testing is required, compliance with the VOC limits specified in Condition D.2.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing. Testing of this facility is not specifically required by this permit. However, this does not preclude testing requirements on this facility under 326 IAC 2-1-4(f) and 326 IAC 2-7-6(1).

D.2.5 Volatile Organic Compounds (VOC)

Compliance with the VOC usage limitations contained in Conditions D.2.1 shall be determined pursuant to 326 IAC 8-1-4(a)(3)(A) and 326 IAC 8-1-2(a)(7) using formulation data supplied by the coating manufacturer. IDEM, OAM reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.2.6 Particulate Matter (PM)

The dry filters for PM control shall be in operation at all times when Glue Booths 5, 6, and 7 are in operation.

D.2.7 Monitoring

- (a) Daily inspections shall be performed at Glue Booths 5, 6, and 7 to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, daily observations shall be made of the overspray while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (b) Weekly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an overspray emission, evidence of overspray emission, or other abnormal emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plans.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.2.8 Record Keeping Requirements

- (a) To document compliance with Condition D.2.1, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC emission limits established in Condition D.2.1.
 - (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) A log of the dates of use;
 - (3) The cleanup solvent usage for each month;
 - (4) The total VOC usage for each month; and
 - (5) The weight of VOCs emitted for each compliance period.
- (b) To document compliance with Conditions D.2.6 and D.2.7, the Permittee shall maintain a log of daily overspray observations, daily and weekly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.2.9 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.2.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported.

SECTION D.3

FACILITY OPERATION CONDITIONS

- (4) One (1) paint at press booth, identified as PPB, equipped with high-volume low-pressure (HVLP) spray applicators with a maximum capacity of 130 plastic automotive parts per hour, with dry filters for overspray control, exhausting to stacks 21 and 22.
- (5) Two (2) glue booths, identified as Glue Booths 22 and 23, equipped with air atomization spray applicators, with dry filters for overspray control, and exhausting to stack 20 and two (2) bolster wrap machines, identified as Bolster Wraps 24 and 25, equipped with air atomization spray applicators, with dry filters for overspray control, and exhausting to stack 20. The combined maximum capacity of these units is 288 plastic automotive parts per hour.

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Best Available Control Technology (BACT) [326 IAC 8-1-6]

- (a) Pursuant to CP 133-8476-00018, issued on September 11, 1997, the VOC content of the glue supplied to the applicators of Glue Booths 22 and 23 and Bolster Wraps 24 and 25 shall not exceed a combined total of 2.0 tons per month. Compliance with this limit will make 326 IAC 8-1-6 (BACT) not applicable to these facilities.
- (b) Pursuant to CP 133-8476-00018, issued on September 11, 1997, the VOC content delivered to the applicators of the Paint at Press Booth shall not exceed 2.0 tons per month. Compliance with this limit will make 326 IAC 8-1-6 (BACT) not applicable to these facilities.

D.3.2 PSD Minor Source Limit [326 IAC 2-2] [40 CFR 52.21]

The VOC content delivered to the applicator of Glue Booths 22, 23, and 27-29 (specified in Section D.4), Bolster Wraps 24 and 25 and the Paint at Press Booth, shall be such that VOC emissions from these combined facilities shall not exceed 3.25 tons per month. Compliance with these limits makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.3.3 Particulate Matter (PM) [326 IAC 6-3-2(c)]

The PM from Paint Line 2 shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

D.3.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

Compliance Determination Requirements

D.3.5 Testing Requirements [326 IAC 2-7-6(1)]

If testing is required, compliance with the VOC limits specified in Condition D.3.1 and D.3.2 shall be determined by a performance test conducted in accordance with Section C - Performance Testing. Testing of this facility is not specifically required by this permit. However, this does not preclude testing requirements on this facility under 326 IAC 2-1-4(f) and 326 IAC 2-7-6(1).

D.3.6 Volatile Organic Compounds (VOC)

Compliance with the VOC content and usage limitations contained in Conditions D.3.1 and D.3.2 shall be determined pursuant to 326 IAC 8-1-4(a)(3)(A) and 326 IAC 8-1-2(a)(7) using formulation data supplied by the coating manufacturer. IDEM, OAM reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.3.7 Particulate Matter (PM)

The dry filters for PM control shall be in place at all times when Glue Booths 22 and 23, Bolster Wraps 24 and 25 and the Paint at Press Booth are in operation.

D.3.8 Monitoring

- (a) Daily inspections shall be performed at Glue Booths 22 and 23, Bolster Wraps 24 and 25 and the Paint at Press Booth to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, daily observations shall be made of the overspray while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (b) Weekly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an overspray emission, evidence of overspray emission, or other abnormal emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plans.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.3.9 Record Keeping Requirements

- (a) To document compliance with Conditions D.3.1 and D.3.2, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.3.1 and D.3.2.
 - (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) A log of the dates of use;
 - (3) The cleanup solvent usage for each month;
 - (4) The total VOC usage for each month; and

- (5) The weight of VOCs emitted for each compliance period.
- (b) To document compliance with Conditions D.3.7 and D.3.8, the Permittee shall maintain a log of daily overspray observations, daily and weekly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.3.10 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.3.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported.

SECTION D.4

FACILITY OPERATION CONDITIONS

- (6) Three (3) glue booths, identified as Glue Booths 27-29, each with a maximum capacity of 125 plastic and fabric parts per hour, with dry filters for control of particulate matter overspray, with Glue Booth 27 exhausting to stack 13, and Glue Booths 28 and 29 exhausting to stack 23.

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1 AND 40 CFR 52.780, WITH CONDITIONS LISTED BELOW.

Construction Conditions [326 IAC 2-1-3.2]

General Construction Conditions

- D.4.1 This permit to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

Effective Date of the Permit

- D.4.2 Pursuant to 326 IAC 2-1-9(b) (Revocation of Permits), IDEM, OAM, will revoke this section of the approved permit if construction is not commenced within eighteen (18) months after receipt of this permit or if construction is suspended for a continuous period of one (1) year or more.
- D.4.3 All requirements of these construction conditions shall remain in effect unless modified in a manner consistent with procedures established for modifications of construction permits pursuant to 326 IAC 2 (Permit Review Rules).

First Time Operation Permit

- D.4.4 This document shall also become the first-time operation permit for the facilities under this section of this permit, pursuant to 326 IAC 2-1-4 (Operating Permits) when, prior to start of operation, the following requirements are met:
- (a) The attached affidavit of construction shall be submitted to:

Indiana Department of Environmental Management
Permit Administration & Development Section, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

verifying that the facilities were constructed as proposed in the application. The facilities covered in this section of this permit may begin operating on the date the Affidavit of Construction is postmarked or hand delivered to IDEM.
 - (b) If construction is completed in phases; i.e., the entire construction is not done continuously, a separate affidavit must be submitted for each phase of construction. Any permit conditions associated with operation start up dates such as stack testing for New Source Performance Standards (NSPS) shall be applicable to each individual phase.
 - (c) The Permittee shall receive an Operation Permit Validation Letter from the Chief of the Permit Administration & Development Section and attach it to this permit.

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.4.5 Best Available Control Technology (BACT) [326 IAC 8-1-6]

The VOC content of the glue supplied to the applicators of Glue Booths 27, 28 and 29 shall not exceed a combined total of 2.0 tons per month. Compliance with this limit will make 326 IAC 8-1-6 (BACT) and 326 IAC 2-2 (PSD) not applicable to these facilities.

D.4.6 PSD Minor Source Limit [326 IAC 2-2] [40 CFR 52.21]

The VOC content delivered to the applicator of Glue Booths 22, 23, and 27-29, Bolster Wraps 24 and 25 and the Paint at Press Booth (specified in Section D.3), shall be such that VOC emissions from these combined facilities shall not exceed 3.25 tons per month. Compliance with these limits makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

D.4.7 Particulate Matter (PM) [326 IAC 6-3-2(c)]

The PM from the Glue Booths (27-29) shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

D.4.8 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for Glue Booths 27-29, and any control devices.

Compliance Determination Requirements

D.4.9 Testing Requirements [326 IAC 2-7-6(1)]

If testing is required, compliance with the VOC limits specified in Conditions D.4.5 and D.4.6 shall be determined by a performance test conducted in accordance with Section C - Performance Testing. Testing of these facilities are not specifically required by this permit. However, this does not preclude testing requirements on these facilities under 326 IAC 2-1-4(f) and 326 IAC 2-7-6(1).

D.4.10 Volatile Organic Compounds (VOC)

Compliance with the VOC usage limitations contained in Conditions D.4.5 and D.4.6 shall be determined pursuant to 326 IAC 8-1-4(a)(3)(A) and 326 IAC 8-1-2(a)(7) using formulation data supplied by the coating manufacturer. IDEM, OAM reserves the authority to determine compliance using Method 24 in conjunction with the analytical procedures specified in 326 IAC 8-1-4.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.4.11 Particulate Matter (PM)

The dry filters for PM control shall be in operation at all times when Glue Booths 27-29 are in operation.

D.4.12 Monitoring

- (a) Daily inspections shall be performed at Glue Booths 27-29 to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, daily observations shall be made of the overspray while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be

considered a violation of this permit.

- (b) Weekly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an overspray emission, evidence of overspray emission, or other abnormal emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plans.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.4.13 Record Keeping Requirements

- (a) To document compliance with Conditions D.4.5 and D.4.6, the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC emission limits established in Condition D.4.5 and D.4.6.
 - (1) The amount and VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) A log of the dates of use;
 - (3) The cleanup solvent usage for each month;
 - (4) The total VOC usage for each month; and
 - (5) The weight of VOCs emitted for each compliance period.
- (b) To document compliance with Conditions D.4.11 and D.4.12, the Permittee shall maintain a log of daily overspray observations, daily and weekly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.4.14 Reporting Requirements

A quarterly summary of the information to document compliance with Conditions D.4.5 and D.4.6 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported.

SECTION D.5

FACILITY OPERATION CONDITIONS

Insignificant Activities:

- (1) Natural gas-fired combustion sources with heat input equal to or less than ten (10) million Btu per hour (water boiler - 0.78 MMBtu/hr, water boiler - 1.092 MMBtu/hr, comfort heat boiler - 0.745 MMBtu/hr, space heaters).

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.5.1 Particulate Matter (PM) [326 IAC 6-2-4]

Pursuant to 326 IAC 6-2-4 (Particulate Matter Emission Limitations for Sources of Indirect Heating, the PM emissions from the 0.78 MMBtu per hour boiler, the 1.092 MMBtu per hour boiler and the 0.745 MMBtu per hour boiler shall be limited to 0.6 pounds per MMBtu heat input.

Compliance Determination Requirement

D.5.2 Testing Requirements [326 IAC 2-7-6(1)]

If testing is required, compliance with the PM limits specified in Condition D.5.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing. Testing of this facility is not specifically required by this permit. However, this does not preclude testing requirements on this facility under 326 IAC 2-1-4(f) and 326 IAC 2-7-6(1).

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.5.3 Compliance Monitoring

There are no compliance monitoring requirements for these insignificant activities.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.5.4 Record Keeping and Reporting Requirements

There are no record keeping and reporting requirements for these insignificant activities.

SECTION D.6 FACILITY CONDITIONS

Insignificant Activities:

(2) Other categories with emissions below insignificant thresholds:

- (a) Touch-up paint booth in "Ranger" paint room;
- (b) Touch-up paint booth in "S-Van" paint room;
- (c) Touch-up paint hood near pad printing room;
- (d) Mask washer in "Ranger" paint room;

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.6.1 Volatile Organic Compounds (VOC) [326 IAC 8-1-6]

Pursuant to CP 133-2333, issued on January 28, 1992, the insignificant touch-up booth and the mask washer in the "Ranger" paint room have been limited to combined VOC emissions less than 24 tons per year to retain a registered status and so that 326 IAC 8-1-6 does not apply. Any change or modification that would cause an increase in potential emissions above 25 tons per year shall require prior approval by OAM.

D.6.2 Particulate Matter (PM) [326 IAC 6-3]

Pursuant to 326 IAC 6-3 (Process Operations), the allowable PM emission rate from the insignificant painting operations shall not exceed allowable PM emission rate based on the following equation:

Interpolation and extrapolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.6.3 Compliance Monitoring

There are no compliance monitoring requirements for these insignificant activities.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.6.4 Record Keeping and Reporting Requirements

There are no record keeping or reporting requirements for these facilities.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
CERTIFICATION**

Source Name: Lear Corporation, Shenandoah Division
Source Address: 500 North Fillmore Road, Greencastle, IN 46135
Mailing Address: 500 North Fillmore Road, Greencastle, IN 46135
Part 70 Permit No.: T133-5083-00018

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- ☐ Annual Compliance Certification Letter
- ☐ Emergency/Deviation Occurrence Reporting Form
- ☐ Test Result (specify) _____
- ☐ Report (specify) _____
- ☐ Notification (specify) _____
- ☐ Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**P.O. Box 6015
100 North Senate Avenue
Indianapolis, Indiana 46206-6015
Phone: 317-233-5674
Fax: 317-233-5967**

**PART 70 OPERATING PERMIT
EMERGENCY/DEVIATION OCCURRENCE REPORT**

Source Name: Lear Corporation, Shenandoah Division
Source Address: 500 North Fillmore Road, Greencastle, IN 46135
Mailing Address: 500 North Fillmore Road, Greencastle, IN 46135
Part 70 Permit No.: T133-5083-00018

This form consists of 2 pages

Page 1 of 2

Check either No. 1 or No.2	
<input type="checkbox"/> 1.	This is an emergency as defined in 326 IAC 2-7-1(12) <ul style="list-style-type: none">• The Permittee must notify the Office of Air Management (OAM), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and• The Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16
<input type="checkbox"/> 2.	This is a deviation, reportable per 326 IAC 2-7-5(3)(c) <ul style="list-style-type: none">• The Permittee must submit notice in writing within ten (10) calendar days

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency/Deviation:
Describe the cause of the Emergency/Deviation:

If any of the following are not applicable, mark N/A

Date/Time Emergency/Deviation started:
Date/Time Emergency/Deviation was corrected:
Was the facility being properly operated at the time of the emergency/deviation? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency/deviation:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____
Title / Position: _____
Date: _____
Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

Part 70 Quarterly Report

Source Name: Lear Corporation, Shenandoah Division
Source Address: 500 North Fillmore Road, Greencastle, IN 46135
Mailing Address: 500 North Fillmore Road, Greencastle, IN 46135
Part 70 Permit No.: T133-5083-00018
Facility: Paint Line 1 and Paint Line 2
Parameter: VOC emissions
Limit: 10.33 tons per month (equivalent to 124 tons per year) each

YEAR: _____

Month	VOC emission from Paint Line 1 this month	VOC emission from Paint Line 2 this month
Month 1		
Month 2		
Month 3		

- ☐ No deviation occurred in this quarter.
- ☐ Deviation/s occurred in this quarter.
Deviation has been reported on: _____

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

Part 70 Quarterly Report

Source Name: Lear Corporation, Shenandoah Division
Source Address: 500 North Fillmore Road, Greencastle, IN 46135
Mailing Address: 500 North Fillmore Road, Greencastle, IN 46135
Part 70 Permit No.: T133-5083-00018
Facility: Glue Booths 6 and 7, and Glue Booths 10 and 12
Parameter: VOC emissions
Limit: 2.0 tons per month (equivalent to 24 tons per year)

YEAR: _____

Month	Combined VOC emission from Glue Booths 6 and 7 this month	Combined VOC emission from Glue Booths 10 and 12 this month
Month 1		
Month 2		
Month 3		

- ☐ No deviation occurred in this quarter.
- ☐ Deviation/s occurred in this quarter.
Deviation has been reported on: _____

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

Part 70 Quarterly Report

Source Name: Lear Corporation, Shenandoah Division
Source Address: 500 North Fillmore Road, Greencastle, IN 46135
Mailing Address: 500 North Fillmore Road, Greencastle, IN 46135
Part 70 Permit No.: T133-5083-00018
Facility: Glue Booths 22, 23, and 27-29; Bolster Wraps 24 and 25; Paint at Press Booth
Parameter: VOC emissions
Limit: 2.0 tons per month (equivalent to 24 tons per year) combined for Glue Booths 22 and 23, and Bolster Wraps 24 and 25; 2.0 tons per month (equivalent to 24 tons per year) for Paint at Press Booth; and total for Glue Booths 22, 23, 27-29, Bolster Wraps 24 and 25, and Paint at Press Booth of 3.25 tons per month (equivalent to 39 tons per year).

YEAR: _____

Month	Combined VOC emission from Glue Booths 22 and 23 and Bolster Wraps 24 and 25 this month	VOC emissions from Paint at Press Booth this month	VOC emissions from Glue Booths 27-29 this month	Combined VOC emission from Glue Booths 22, 23, 27-29, Bolster Wraps 24 and 25 and Paint at Press Booth this month
Month 1				
Month 2				
Month 3				

- ☐ No deviation occurred in this quarter.
- ☐ Deviation/s occurred in this quarter.
Deviation has been reported on: _____

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
QUARTERLY COMPLIANCE REPORT**

Source Name: Lear Corporation, Shenandoah Division
Source Address: 500 North Fillmore Road, Greencastle, IN 46135
Mailing Address: 500 North Fillmore Road, Greencastle, IN 46135
Part 70 Permit No.: T133-5083-00018

Months: _____ **to** _____ **Year:** _____

This report is an affirmation that the source has met all the requirements stated in this permit. This report shall be submitted quarterly. Any deviation from the requirements and the date(s) of each deviation must be reported. Additional pages may be attached if necessary. This form can be supplemented by attaching the Emergency/Deviation Occurrence Report. If no deviations occurred, please specify zero in the column marked "No Deviations".

LIST EACH COMPLIANCE REQUIREMENT EXISTING FOR THIS SOURCE:

Requirement (e.g. permit condition D.1.3)	Number of Deviations	Date of each Deviations	No Deviations

Form Completed By: _____
Title/Position: _____
Date: _____
Phone: _____

Attach a signed certification to complete this report.

Indiana Department of Environmental Management Office of Air Management

Technical Support Document (TSD) for a Part 70 Operating Permit and Enhanced New Source Review

Source Background and Description

Source Name:	Lear Corporation, Shenandoah Division
Source Location:	500 North Fillmore Road, Greencastle, IN 46135
County:	Putnam
SIC Code:	3089
Operation Permit No.:	T133-5083-00018
Permit Reviewer:	Dana L. Brown

The Office of Air Management (OAM) has reviewed a Part 70 permit application from Lear Corporation, Shenandoah Division, relating to the operation of a plant for the manufacturing of injection molded plastic parts for use in automobile interiors.

Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

- (1) One Ranger paint application line, identified as Paint Line 1, consisting of two (2) paint booths, 1 and 2, and one (1) curing oven, with a maximum capacity of 360 plastic parts per hour, with particulate matter overspray from each booth controlled by water curtain, and exhausting to stacks 1 and 2.
- (2) One S-Van paint application line, identified as Paint Line 2, consisting of two (2) paint booths, 3 and 4, and one (1) curing oven, with a maximum capacity of 420 plastic parts per hour, with particulate matter overspray from each booth controlled by water curtain, and exhausting to stacks 3, 4, and 5.
- (3) Nine (9) glue booths, identified as Glue Booth 1-7, 10 and 12, each with a maximum capacity of 125 plastic and fabric parts per hour, and exhausting to stacks 10, 12, 13, and 14. Glue Booths 5, 6, and 7 use dry filters for particulate matter overspray control.
- (4) One (1) paint at press booth, identified as PPB, equipped with high-volume low-pressure (HVLP) spray applicators with a maximum capacity of 130 plastic automotive parts per hour, with dry filters for overspray control, exhausting to stacks 21 and 22.
- (5) Two (2) glue booths, identified as Glue Booths 22 and 23, equipped with air atomization spray applicators, with dry filters for overspray control, and exhausting to stack 20 and two (2) bolster wrap machines, identified as Bolster Wraps 24 and 25, equipped with air atomization spray applicators, with dry filters for overspray control, and exhausting to stack 20. The combined maximum capacity of these units is 288 plastic automotive parts per hour.
- (6) The storage, handling, and processing of plastic resins produce fugitive emissions.

Unpermitted Emission Units and Pollution Control Equipment

There are no unpermitted facilities operating at this source during this review process.

Emission Units and Pollution Control Equipment Under Enhanced New Source Review (ENSR)

The application includes information relating to the construction and operation of the following equipment:

- (1) Three (3) glue booths, identified as Glue Booths 27-29, each with a maximum capacity of 125 plastic and fabric parts per hour, with dry filters for control of particulate matter overspray, with Glue Booth 27 exhausting to stack 13, and Glue Booths 28 and 29 exhausting to stack 23.

Insignificant Activities

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (1) Natural gas-fired combustion sources with heat input equal to or less than ten (10) million Btu per hour (water boiler - 0.78 MMBtu/hr, water boiler - 1.092 MMBtu/hr, comfort heat boiler - 0.745 MMBtu/hr, space heaters).
- (2) Propane or liquefied petroleum gas, or butane-fired combustion sources with heat input equal to or less than six million (6,000,000) Btu per hour (liquid propane torches).
- (3) Water based adhesives that are less than or equal to 5% by volume of VOCs, excluding HAPs. (2 glue booths using salt water activated adhesives)
- (4) A laboratory as defined in 326 IAC 2-7(20)(c).
- (5) Other categories with emissions below insignificant thresholds:
 - (a) Touch-up paint booth in "Ranger" paint room;
 - (b) Touch-up paint booth in "S-Van" paint room;
 - (c) Touch-up paint hood near pad printing room;
 - (d) Mask washer in "Ranger" paint room;

Existing Approvals

The source has been operating under the following approvals:

- (1) OP 67-02-92-0112, issued on March 1, 1988;
- (2) OP 3520-0018-0132, issued on June 27, 1990;
- (3) CP 133-2333-00018, issued on January 28, 1992;
- (4) CP 133-2380-00018, issued on April 21, 1992; and
- (5) CP 133-8476-00018, issued on September 11, 1997.

Enforcement Issue

There are no Enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the Part 70 permit be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete Part 70 permit application for the purposes of this review was received on December 1, 1995. Additional information was received on July 31, 1996.

A notice of completeness letter was mailed to the source on December 3, 1996.

Potential Emissions

Pursuant to 326 IAC 1-2-55, Potential Emissions are defined as "emissions of any one (1) pollutant which would be emitted from a facility, if that facility were operated without the use of pollution control equipment unless such control equipment is necessary for the facility to produce its normal product or is integral to the normal operation of the facility."

Pollutant	Potential Emissions (tons/year)
PM	greater than 100, less than 250
PM-10	greater than 100, less than 250
SO ₂	less than 100
VOC	greater than 100, greater than 25
CO	less than 100
NO _x	less than 100

Note: For the purpose of determining Title V applicability for particulates, PM-10, not PM, is the regulated pollutant in consideration.

HAP's	Potential Emissions (tons/year)
Toluene	greater than 10
Methanol	less than 10
Ethyl Benzene	greater than 10
Methyl Isobutyl Ketone	greater than 10
Xylene	greater than 10
Glycol Ethers	greater than 10
TOTAL	greater than 25

- (a) The potential emissions (as defined in the Indiana Rule) of PM-10 and VOC are equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) The potential emissions (as defined in Indiana Rule) of any single HAP are equal to or greater than ten (10) tons per year and the potential emissions (as defined in Indiana Rule) of a combination HAPs are greater than or equal to twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (c) Fugitive Emissions
Since this type of operation is not one of the 28 listed source categories under 326 IAC 2-2 and since there are no applicable New Source Performance Standards that were in

effect on August 7, 1980, the fugitive particulate matter (PM) and volatile organic compound (VOC) emissions are not counted toward determination of PSD and Emission Offset applicability.

Actual Emissions

The following table shows the actual emissions from the source. This information reflects the 1994 OAM emission data.

Pollutant	Actual Emissions (tons/year)
PM	22.51
PM-10	0.0
SO ₂	0.0
VOC	206.451
CO	0.0
NO _x	0.0
HAP (specify)	Not Available

Limited Potential to Emit

The table below summarizes the total limited potential to emit of the significant emission units.

	Limited Potential to Emit (tons/year)	
Process/facility	VOC	
Paint Line 1	124	
Paint Line 2	124	
Insignificant paint booth in “Ranger” paint room	24	
Glue Booths 6 and 7	24	
Glue Booths 10 and 12	24	
Paint at Press Booth	24	39
Glue Booths 22 & 23 and Bolster Wraps 24 & 25	24	
Glue Booths 27, 28 and 29	24	
Total Emissions	383	

County Attainment Status

The source is located in Putnam County.

Pollutant	Status
TSP	Attainment
PM-10	Attainment
SO ₂	Attainment
NO ₂	Attainment
Ozone	Attainment
CO	Attainment
Lead	Attainment

- (a) Volatile organic compounds (VOC) and oxides of nitrogen are precursors for the formation of ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to the ozone standards. Putnam County has been designated as attainment or unclassifiable for ozone.

Part 70 Permit Conditions

This source is subject to the requirements of 326 IAC 2-7, pursuant to which the source has to meet the following:

- (1) Emission limitations and standards, including those operational requirements and limitations that assure compliance with all applicable requirements at the time of issuance of Part 70 permits.
- (2) Monitoring and related record keeping requirements which assume that all reasonable information is provided to evaluate continuous compliance with the applicable requirements.

Federal Rule Applicability

- (a) The three (3) insignificant natural gas boilers, with capacities of 1.092 MMBtu per hour, 0.78 MMBtu per hour and 0.75 MMBtu per hour are not subject to the requirements of the New Source Performance Standard, 326 IAC 12, (40 CFR 60.40c, Subpart Dc), because the boilers are all smaller than the 10 MMBtu per hour applicability of the rule.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAP) applicable to this source.

State Rule Applicability - Entire Source

326 IAC 2-2 (Prevention of Significant Deterioration)

This source is a major PSD source that has accepted limits out of PSD applicability. Paint Line 1 has been limited to 124 tons per year of VOC emissions, Paint Line 2 has been limited to 124 tons per year of VOC emissions. Modifications to the source have all been minor modifications, therefore the source has never undergone a PSD review. The addition of Glue Booths 27-29 under Enhanced New Source Review as part of this permit will be limited to 24 tons per year of combined VOC emissions, to be considered as a minor modification.

326 IAC 2-6 (Emission Reporting)

This source is subject to 326 IAC 2-6 (Emission Reporting), because it has the potential to emit more than one hundred (100) tons per year of PM-10 and VOC. Pursuant to this rule, the owner/operator of the source must annually submit an emission statement for the source. The annual statement must be received by July 1 of each year and contain the minimum requirement as specified in 326 IAC 2-6-4. The submittal should cover the period defined in 326 IAC 2-6-2(8) (Emission Statement Operating Year).

326 IAC 5-1 (Visible Emissions Limitations)

Pursuant to 326 IAC 5-1-2 (Visible Emissions Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), visible emissions shall meet the following, unless otherwise stated in this permit:

- (a) Visible emissions shall not exceed an average of forty percent (40%) opacity in twenty-four (24) consecutive readings as determined by 326 IAC 5-1-4,
- (b) Visible emissions shall not exceed sixty percent (60%) opacity for more than a cumulative total of fifteen (15) minutes (sixty (60) readings) in a six (6) hour period.

State Rule Applicability - Individual Facilities

326 IAC 6-2 (Particulate Matter Limitations for Sources of Indirect Heat)

The three (3) insignificant boilers were all constructed after September 21, 1983. Pursuant to 326 IAC 6-2-4, all indirect heating facilities constructed after September 21, 1983 shall be limited by the following:

$$Pt = \frac{1.09}{Q^{0.26}} \quad \text{Where } Pt = \text{particulate matter emitted (lb/MMBtu);}$$
$$Q = \text{source maximum operating capacity rating (MMBtu/hr)}$$

For the 1.092 MMBtu per hour boiler, built in 1989, $Q = 1.092$:

$$Pt = \frac{1.09}{Q^{0.26}} = \frac{1.09}{1.023} = 1.06 \text{ lb/MMBtu}$$

For the 0.78 MMBtu per hour boiler, built in 1992, $Q = 1.872$:

$$Pt = \frac{1.09}{Q^{0.26}} = \frac{1.09}{1.169} = 0.93 \text{ lb/MMBtu}$$

For the 0.745 MMBtu per hour boiler, built in 1996, $Q = 2.622$:

$$Pt = \frac{1.09}{Q^{0.26}} = \frac{1.09}{1.272} = 0.85 \text{ lb/MMBtu}$$

Pursuant to 326 IAC 6-2-4, Pt shall not exceed 0.6 pounds per MMBtu when Q is less than 10 MMBtu per hour, therefore, the three (3) boiler are each limited to 0.6 pounds per MMBtu.

Potential emissions for the 1.092 MMBtu per hour boiler are:

$$\frac{0.1 \text{ tons}}{\text{year}} \times \frac{1 \text{ year}}{8760 \text{ hrs}} \times \frac{1 \text{ hour}}{1.092 \text{ MMBtu}} \times \frac{2000 \text{ lbs}}{1 \text{ ton}} = \frac{0.020 \text{ lbs}}{\text{MMBtu}}$$

Potential emissions for the 0.78 MMBtu per hour boiler and the 0.745 MMBtu per hour boiler are negligible. Therefore, all three (3) boilers are in compliance with 326 IAC 6-2-4.

326 IAC 6-3-2 (Process Operations)

Particulate matter (PM) overspray from all of the spray coating operations shall be limited by the following:

Interpolation and extrapolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour and
P = process weight rate in tons per hour

The source uses dry filters or water curtain at each of the spray coating booths in order to comply with this rule.

326 IAC 8-1-6 (Best Available Control Technology)

- (1) The spray booths in Paint Line 1 and Paint Line 2 are subject to and shall meet BACT requirements. Pursuant to OP 3520-0018-0132, issued on June 27, 1990, BACT has been determined to be, the use of low pressure-high volume spray equipment with a transfer efficiency of no less than fifty-five percent (55%) and use of coatings containing no greater than 6.1 pounds of VOC per gallon less water.
- (2) Pursuant to Registration CP 133-2333-00018, issued on January 28, 1992, the insignificant touch-up booth in the "Ranger" paint room has been limited to VOC emissions less than 24 tons per year to have registered status and so that 326 IAC 8-1-6 does not apply.
- (3) Pursuant to CP 133-2380-00018, issued on April 21, 1992, Glue Booths 6 and 7 have been limited to a combined VOC emissions of 24 tons per year so that 326 IAC 8-1-6 does not apply.
- (4) Glue Booths 10 and 12 will be limited by this permit to combined VOC emissions of 24 tons per year so that 326 IAC 8-1-6 does not apply.
- (5) Pursuant to CP 133-8476-00018, issued on September 11, 1997, Glue Booths 22 and 23 and Bolster Wraps 24 and 25 have been limited to combined VOC emissions of 24 tons per year so that 326 IAC 8-1-6 does not apply.
- (6) Pursuant to CP 133-8476-00018, issued on September 11, 1997, the Paint at Press Booth has been limited to VOC emissions of 24 tons per year so that 326 IAC 8-1-6 does not apply.
- (7) Potential emissions of VOC from Glue Booths 27, 28, and 29 are less than 25 tons per year, therefore 326 IAC 8-1-6 will not apply to these facilities.

Compliance Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAM, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in permit Section D are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also in permit Section D. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for response steps and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate response steps within a specific time

period.

The compliance monitoring requirements applicable to this source are as follows:

- (1) Paint Line 1 and Paint Line 2 have applicable compliance monitoring conditions as specified below:
 - (a) Daily inspections to verify that the scrubber water flow rate is sufficient to produce a uniform water curtain.

These monitoring conditions are necessary ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-2 (PSD).

- (2) Glue Booths 5, 6 and 7, Glue Booths 27-29, Glue Booths 22 and 23, Bolster Wraps 24 and 25 and the Paint at Press Booth have applicable compliance monitoring conditions as specified below:
 - (a) Daily inspections to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, daily observations shall be made of the overspray while one or more of the booths are in operation.
 - (b) Weekly inspections of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground.

These monitoring conditions are necessary ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-2 (PSD).

Air Toxic Emissions

Indiana presently requests applicants to provide information on emissions of the 187 hazardous air pollutants set out in the Clean Air Act Amendments of 1990. These pollutants are either carcinogenic or otherwise considered toxic and are commonly used by industries. They are listed as air toxics on the Office of Air Management (OAM) Part 70 Application Form GSD-08.

- (a) This source will emit levels of air toxics greater than those that constitute major source applicability according to Section 112 of the Clean Air Act.

Conclusion

The operation of this plant, manufacturing injection molded plastic parts for use in automobile interiors, shall be subject to the conditions of the attached proposed **Part 70 Permit No. T133-5083-00018**.

Appendix A: Emissions Calculations

**VOC and Particulate
From Glue Booths**

Company Name: Lear Corporation - Shenandoah Division
Address City IN Zip: 500 North Filmore Road, Greencastle, Indiana 46135
T: 133-5083
Plt ID: 00018
Reviewer: Dana L. Brown
Date: October 6, 1997

Material	Density (Lb/Gal)	Weight% Volatile (H2O& Organics)	Weight% Water	Weight% Organics	Volume % Water	Volume % Non-Vol (solids)	Gal of Mat (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating	Potential VOC pounds per hour	Potential VOC pounds per day	Potential VOC tons per year	Particulate Potential ton/yr	Lb VOC /gal solids	Transfer Efficiency
Fastbond 2000 NF	9.2	50.00%	46.6%	3.4%	51.3%	45.00%	0.00330	125.000	0.63	0.31	0.13	3.06	0.56	8.30	0.69	0%
Fastbond	9.5	85.00%	85.0%	0.0%	96.9%	3.10%	0.00060	125.000	0.00	0.00	0.00	0.00	0.00	0.47	0.00	0%
Spray	6.9	72.20%	0.0%	72.2%	0.0%	23.00%	0.00260	125.000	5.00	5.00	1.63	39.03	7.12	2.74	21.75	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%
	0.0	0.00%	0.0%	0.0%	0.0%	0.00%	0.00000	0.000	0.00	0.00	0.00	0.00	0.00	0.00	ERR	0%

State Potential Emissions

Add worst case coating to all solvents

1.75

42.08

7.68

11.51

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)

Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)

Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)

Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)

Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)

Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) * (8760 hrs/yr) * (1 ton/2000 lbs)

Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Total = Worst Coating + Sum of all solvents used

Indiana Department of Environmental Management Office of Air Management

Addendum to the Technical Support Document for Part 70 Operating Permit and Enhanced New Source Review (ENSR)

Source Name:	Lear Corporation, Shenandoah Division
Source Location:	500 North Fillmore Road, Greencastle, IN 46135
County:	Putnam
SIC Code:	3089
Operation Permit No.:	T133-5083-00018
Permit Reviewer:	Dana L. Brown

On November 6, 1997, the Office of Air Management (OAM) had a notice published in The Banner Graphic, Greencastle, Indiana, stating that Lear Corporation, Shenandoah Division had applied for a Part 70 Operating Permit to operate a plant for the manufacturing of injection molded plastic parts for use in automobile interiors. The notice also stated that OAM proposed to issue a permit for this operation and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

Upon further review, OAM has made the following changes to the final Part 70 permit (changes are bolded for emphasis):

1. Construction applications for the Paint at Press Booth, Glue Booths 22, 23, and 27-29, and Bolster Wraps 24 and 25 were received within one (1) year of one another, therefore, under EPA policy these units should be combined as one modification to a major source for the purposes of 326 IAC 2-2 (PSD). The following changes have been made to the permit:

- (a) Condition D.3.2 on page 35 of 49 of the proposed permit has been changed from:

D.3.2 PSD Minor Source Limit [326 IAC 2-2] [40 CFR 52.21]

Pursuant to CP 133-8476-00018, issued on September 11, 1997, the VOC content delivered to the applicator of Glue Booths 22 and 23, Bolster Wraps 24 and 25 and the Paint at Press Booth, shall be such that VOC emissions from these combined facilities shall not exceed 3.25 tons per month. Compliance with these limits makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

to be as follows on page 35 of 49 of the final permit:

D.3.2 PSD Minor Source Limit [326 IAC 2-2] [40 CFR 52.21]

The VOC content delivered to the applicator of **Glue Booths 22, 23, and 27-29 (specified in Section D.4)**, Bolster Wraps 24 and 25 and the Paint at Press Booth, shall be such that VOC emissions from these combined facilities shall not exceed 3.25 tons per month. Compliance with these limits makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

- (b) The following condition has been added as Condition D.4.6 on page 39 of 49 of the final permit:

D.4.6 PSD Minor Source Limit [326 IAC 2-2] [40 CFR 52.21]

The VOC content delivered to the applicator of Glue Booths 22, 23, and 27-29, Bolster Wraps 24 and 25 and the Paint at Press Booth (specified in Section D.3), shall be such that VOC emissions from these combined facilities shall not exceed 3.25 tons per month. Compliance with these limits makes 326 IAC 2-2 (Prevention of Significant Deterioration) not applicable.

Subsequent conditions have been renumbered, and the report form on page 48 of 49 of the final permit has been updated to show compliance with the new combined limit.

Please note the following changes to the original TSD:

- (a) The appropriate rows of the limited potential to emit table on page 4 of 8 of the TSD should be changed from:

Paint at Press Booth	24	39
Glue Booths 22 & 23 and Bolster Wraps 24 & 25	24	
Glue Booths 27, 28 and 29	24	

to be as follow, to show the combination of units:

Paint at Press Booth	24	39
Glue Booths 22 & 23 and Bolster Wraps 24 & 25	24	
Glue Booths 27, 28 and 29	24	

- (b) The rule explanation for 326 IAC 2-2, on page 5 of 8 of the TSD should be changed from:

326 IAC 2-2 (Prevention of Significant Deterioration)

This source is a major PSD source that has accepted limits out of PSD applicability. Paint Line 1 has been limited to 124 tons per year of VOC emissions, Paint Line 2 has been limited to 124 tons per year of VOC emissions. Modifications to the source have all been minor modifications, therefore the source has never undergone a PSD review. The addition of Glue Booths 27-29 under Enhanced New Source Review as part of this permit will be limited to 24 tons per year of combined VOC emissions, to be considered as a minor modification.

to be as follows:

326 IAC 2-2 (Prevention of Significant Deterioration)

This source is a major PSD source that has accepted limits out of PSD applicability. Paint Line 1 has been limited to 124 tons per year of VOC emissions, Paint Line 2 has been limited to 124 tons per year of VOC emissions. Modifications to the source have all been minor modifications, therefore the source has never undergone a PSD review. The addition of Glue Booths 27-29 under Enhanced New Source Review as part of this permit will be **combined with Glue Booths 22 and 23, Bolster Wraps 24 and 25, and the Paint at Press booth**, and limited to 39 tons per year of combined VOC emissions, to be considered as a minor modification. These units have a combined limit because they have construction permit applications for these units were received within a one (1) year time frame.

2. Condition D.3.9(b) on page 37 of 49 of the original permit, has been corrected for the appropriate compliance provisions of this facility. Condition D.3.9(b) will be changed from:

(b) To document compliance with Conditions D.3.7 and D.3.8, the Permittee shall maintain a log of daily water curtain inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.

to be as follows on page 37 of 49 of the final permit:

(b) To document compliance with Conditions D.3.7 and D.3.8, the Permittee shall maintain a log of daily **overspray observations, daily and weekly inspections**, and those additional inspections prescribed by the Preventive Maintenance Plan.

3. Subsection (a) of Condition B.11 (Annual Compliance Certification), on page 9 of 49 of the original permit, has changed from:

(a) The Permittee shall annually certify that the source has complied with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

to be as follows on page 9 of 49 of the final permit:

(a) The Permittee shall annually **submit a compliance certification report which addresses the status of the source's compliance** with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

4. The statement "This condition is not federally enforceable" has been removed from Conditions C.2 (Opacity), and C.4 (Incineration), on page 20 of 49 of the draft permit.

5. The last sentence of Condition C.3 (Open Burning), on page 20 of 49 of the draft permit has been changed from:

This condition is not federally enforceable.

to be as follows on page 20 of 49 of the final permit:

326 IAC 4-1-3(a)(2)(A) and (B) are not federally enforceable.

6. The last sentence of Condition C.5 (Fugitive Dust Emissions), on page 20 of 49 of the draft permit has been changed from:

This condition is not federally enforceable.

to be as follows on page 20 of 49 of the final permit:

326 IAC 6-4-2(4) is not federally enforceable.

7. Condition C.20 (General Reporting Requirements), on page 27 of 49 of the draft permit, has been changed from:

C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

-
- (a) Reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) Unless otherwise specified in this permit, any quarterly report shall be submitted within thirty (30) days of the end of the reporting period.
- (d) All instances of deviations must be clearly identified in such reports. A reportable deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:
- (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
 - (2) An emergency as defined in 326 IAC 2-7-1(12); or
 - (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
 - (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.
- A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred or failure to monitor or record the required compliance monitoring is a deviation.
- (e) Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.
- (f) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.

to be as follows, on page 27 of 49 of the final permit:

C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

- (a) **To affirm that the source has met all the requirements stated in this permit, the source shall submit a Quarterly Compliance Report. Any deviation from the requirements and the date(s) of each deviation must be reported.**
- (b) **The report required in (a) of this condition, and reports required by conditions in Section D of this permit, shall be submitted to:**

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management

100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (c)** Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (d)** Unless otherwise specified in this permit, any quarterly report shall be submitted within thirty (30) days of the end of the reporting period.
- (e)** All instances of deviations must be clearly identified in such reports. A reportable deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:

 - (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
 - (2) An emergency as defined in 326 IAC 2-7-1(12); or
 - (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
 - (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred or failure to monitor or record the required compliance monitoring is a deviation.
- (f)** Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.
- (g)** The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.